



The Span Tables below have been created in accordance with EN 1993-1-3 (Eurocode EC3) and calculated by the Steel Construction Institute (SCI). The values are based on a maximum permitted deflection of Span/150 under imposed load.

Load factor (working load to ultimate) 1.5 (in accordance with Eurocode).
Deflection for limit of span L/150

| | |
|--|--------------|
| POSITIVE loads parameters | 0.5mm |
| Bottom flange in compression | |
| Moment capacity (kNm/m) | 0.824 |
| Inertia (cm ⁴ /m) | 7.288 |
| Bottom flange in tension | |
| Moment capacity (kNm/m) | 0.697 |
| Inertia (cm ⁴ /m) | 7.29 |
| Shear resistance (kN/m) | 19.953 |
| Web crushing mid (kN/m) | 4.903 |
| Web crushing end (kN/m) | 2.452 |
| Inertia gross section (cm ⁴ /m) | 8.596 |

Proclad 1000/32 - 0.5mm **Span/Load Table - POSITIVE - Working load UDL (kN/m²)**

| POSITIVE | | Span in Metres | | | | | | | | | | | | |
|-----------------|-----------------|----------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| Span Type | Design Case | 1.0 | 1.1 | 1.2 | 1.3 | 1.4 | 1.5 | 1.6 | 1.7 | 1.8 | 1.9 | 2.0 | 2.1 | 2.2 |
| Single | Moment | 3.72 | 3.07 | 2.58 | 2.20 | 1.90 | 1.65 | 1.45 | 1.29 | 1.15 | 1.03 | 0.93 | 0.84 | 0.77 |
| | Inertia | 8.31 | 6.24 | 4.81 | 3.78 | 3.03 | 2.46 | 2.03 | 1.69 | 1.42 | 1.21 | 1.04 | 0.90 | 0.78 |
| | Reaction | 3.27 | 2.97 | 2.72 | 2.51 | 2.34 | 2.18 | 2.04 | 1.92 | 1.82 | 1.72 | 1.63 | 1.56 | 1.49 |
| | Limiting | 3.27 | 2.97 | 2.58 | 2.20 | 1.90 | 1.65 | 1.45 | 1.29 | 1.15 | 1.03 | 0.93 | 0.84 | 0.77 |
| Double | Moment | 4.39 | 3.63 | 3.05 | 2.60 | 2.24 | 1.95 | 1.72 | 1.52 | 1.36 | 1.22 | 1.10 | 1.00 | 0.91 |
| | Inertia | 13.84 | 10.40 | 8.01 | 6.30 | 5.05 | 4.10 | 3.38 | 2.82 | 2.37 | 2.02 | 1.73 | 1.49 | 1.30 |
| | Reaction | 2.61 | 2.38 | 2.18 | 2.01 | 1.87 | 1.74 | 1.63 | 1.54 | 1.45 | 1.38 | 1.31 | 1.25 | 1.19 |
| | Interaction | 2.05 | 1.80 | 1.59 | 1.42 | 1.27 | 1.15 | 1.05 | 0.96 | 0.88 | 0.81 | 0.75 | 0.69 | 0.64 |
| Limiting | 2.05 | 1.80 | 1.59 | 1.42 | 1.27 | 1.15 | 1.05 | 0.96 | 0.88 | 0.81 | 0.75 | 0.69 | 0.64 | |
| Multiple | Moment | 5.49 | 4.54 | 3.81 | 3.25 | 2.80 | 2.44 | 2.15 | 1.90 | 1.70 | 1.52 | 1.37 | 1.25 | 1.13 |
| | Inertia | 13.84 | 10.40 | 8.01 | 6.30 | 5.05 | 4.10 | 3.38 | 2.82 | 2.37 | 2.02 | 1.73 | 1.49 | 1.30 |
| | Reaction | 2.97 | 2.70 | 2.48 | 2.29 | 2.12 | 1.98 | 1.86 | 1.75 | 1.65 | 1.56 | 1.49 | 1.42 | 1.35 |
| | Interaction | 2.41 | 2.12 | 1.88 | 1.68 | 1.51 | 1.37 | 1.24 | 1.14 | 1.05 | 0.96 | 0.89 | 0.83 | 0.77 |
| Limiting | 2.41 | 2.12 | 1.88 | 1.68 | 1.51 | 1.37 | 1.24 | 1.14 | 1.05 | 0.96 | 0.89 | 0.83 | 0.77 | |

Load factor (working load to ultimate) 1.5 (in accordance with Eurocode).
Deflection for limit of span L/150

| | |
|--|--------------|
| NEGATIVE loads parameters | 0.5mm |
| Bottom flange in compression | |
| Moment capacity (kNm/m) | 0.697 |
| Inertia (cm ⁴ /m) | 7.29 |
| Bottom flange in tension | |
| Moment capacity (kNm/m) | 0.824 |
| Inertia (cm ⁴ /m) | 7.288 |
| Shear resistance (kN/m) | 19.953 |
| Web crushing mid (kN/m) | 4.903 |
| Web crushing end (kN/m) | 2.452 |
| Inertia gross section (cm ⁴ /m) | 8.596 |

Proclad 1000/32 - 0.5mm **Span/Load Table - NEGATIVE - Working load UDL (kN/m²)**

| NEGATIVE | | Span in Metres | | | | | | | | | | | | |
|-----------------|-----------------|----------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| Span Type | Design Case | 1.0 | 1.1 | 1.2 | 1.3 | 1.4 | 1.5 | 1.6 | 1.7 | 1.8 | 1.9 | 2.0 | 2.1 | 2.2 |
| Single | Moment | 4.39 | 3.63 | 3.05 | 2.60 | 2.24 | 1.95 | 1.72 | 1.52 | 1.36 | 1.22 | 1.10 | 1.00 | 0.91 |
| | Inertia | 8.30 | 6.24 | 4.81 | 3.78 | 3.03 | 2.46 | 2.03 | 1.69 | 1.42 | 1.21 | 1.04 | 0.90 | 0.78 |
| | Reaction | 3.27 | 2.97 | 2.72 | 2.51 | 2.34 | 2.18 | 2.04 | 1.92 | 1.82 | 1.72 | 1.63 | 1.56 | 1.49 |
| | Limiting | 3.27 | 2.97 | 2.72 | 2.51 | 2.24 | 1.95 | 1.72 | 1.52 | 1.36 | 1.21 | 1.04 | 0.90 | 0.78 |
| Double | Moment | 3.72 | 3.07 | 2.58 | 2.20 | 1.90 | 1.65 | 1.45 | 1.29 | 1.15 | 1.03 | 0.93 | 0.84 | 0.77 |
| | Inertia | 13.84 | 10.40 | 8.01 | 6.30 | 5.04 | 4.10 | 3.38 | 2.82 | 2.37 | 2.02 | 1.73 | 1.49 | 1.30 |
| | Reaction | 2.61 | 2.38 | 2.18 | 2.01 | 1.87 | 1.74 | 1.63 | 1.54 | 1.45 | 1.38 | 1.31 | 1.25 | 1.19 |
| | Interaction | 1.92 | 1.68 | 1.48 | 1.31 | 1.18 | 1.06 | 0.96 | 0.88 | 0.80 | 0.74 | 0.68 | 0.63 | 0.58 |
| Limiting | 1.92 | 1.68 | 1.48 | 1.31 | 1.18 | 1.06 | 0.96 | 0.88 | 0.80 | 0.74 | 0.68 | 0.63 | 0.58 | |
| Multiple | Moment | 4.65 | 3.84 | 3.23 | 2.75 | 2.37 | 2.07 | 1.82 | 1.61 | 1.43 | 1.29 | 1.16 | 1.05 | 0.96 |
| | Inertia | 13.84 | 10.40 | 8.01 | 6.30 | 5.04 | 4.10 | 3.38 | 2.82 | 2.37 | 2.02 | 1.73 | 1.49 | 1.30 |
| | Reaction | 2.97 | 2.70 | 2.48 | 2.29 | 2.12 | 1.98 | 1.86 | 1.75 | 1.65 | 1.56 | 1.49 | 1.42 | 1.35 |
| | Interaction | 2.27 | 1.98 | 1.75 | 1.56 | 1.40 | 1.26 | 1.15 | 1.05 | 0.96 | 0.88 | 0.81 | 0.75 | 0.70 |
| Limiting | 2.27 | 1.98 | 1.75 | 1.56 | 1.40 | 1.26 | 1.15 | 1.05 | 0.96 | 0.88 | 0.81 | 0.75 | 0.70 | |



'SCI Assessed Quality Mark'. This mark testifies that the [Steel Construction Institute \(SCI\)](http://www.sci.co.uk) has independently verified the technical data above.